

# Nativa.



E: sales@qcg.co.nz | W: www.qcg.co.nz | P: 0800 525 585



Nativa brings simple elegance to contemporary spaces with the warm delicate beauty of travertine. With visual depth and rich tactile experience, this stunning porcelain collection offers an array of patterns, surfaces and formats in both cross-cut and vein-cut aesthetics.

**PRODUCT TYPE:** Glazed Porcelain

**COLOURS:** See colour options overleaf

**SIZES<sup>(1)</sup>:** 600x1200

**SURFACES:** Natural

**EDGES:** Rectified

**USAGE:** Suitable for floors and walls

**TECHNICAL INFO:** See overleaf

**VARIATION<sup>(2)</sup>:** V3

**WARRANTY<sup>(3)</sup>:** 15 Years

**ORIGIN:** Italy

(1) Sizes are nominal and may include a grout joint. (2) Variation is an inherent property of tiles and stone. (3) If further details are required regarding our warranty or terms please contact our team on sales@qcg.co.nz or 0800 525 585

# Nativa.



E: sales@qcg.co.nz | W: www.qcg.co.nz | P: 0800 525 585

## COLOURS:



Lux



Aurum




Tibur



Lapillo

## SIZES:



600x1200

## TECHNICAL CHARACTERISTICS STANDARD

## VALUE

Compliant with standards EN 14411 annex G group Bla. Compliant with standards ISO 13006 annex G group Bla.

|  |                     |                        |                      |
|--|---------------------|------------------------|----------------------|
|  | Water absorption    | EN ISO 10545-3         | ≤0.5%                |
|  | Frost Resistance    | EN ISO 10545-12        | ✓                    |
|  | Chemical resistance | EN ISO 10545-13        | ✓                    |
|  | Size variation      | EN ISO 10545-2         | -                    |
|  | Thickness           | -                      | 9mm                  |
|  | Hardness (MOHS)     | EN 101                 | -                    |
|  | Faces               | -                      | 15                   |
|  | Breaking Strength   | EN ISO 10545-4         | -                    |
|  |                     |                        |                      |
|  |                     |                        |                      |
|  | Slip Resistance     | DIN 51130 (R) *        | Anti-slip<br>Natural |
|  |                     | AS/NZS 4586:2013 (SRV) | -                    |
|  |                     | Average BP (P)         | -                    |